


APPENDIX G

Lackawanna Cut-Off Restoration – Passenger Rail Study

STRUCTURE INSPECTION REPORT

LACKAWANNA COUNTY - PNRRA
INSPECTION AND ANALYSIS REPORT
PNRRA OVER SLATEFORD CREEK &
STONE MASONRY RETAINING WALL ALONG S.R. 0611
NORTHAMPTON COUNTY
UPPER MOUNT BETHEL TOWNSHIP



Prepared By: Michael J. Ergler, P.E., C.B.S.I.

Inspection By: Michael J. Ergler, P.E., C.B.S.I.
Kris Harvey

Inspection Date: May 24, 2019



52 Glenmaura National Blvd Suite 302
P.O. Box 5777
Scranton, PA 18505
Tel: (570) 342-3700 Fax: (570) 342-4080
www.gpinet.com
An Equal Opportunity Employer


INTENTIONALLY BLANK

TABLE OF CONTENTS

LOCATION MAP	1
GENERAL INFORMATION	2
BRIDGE DESCRIPTION.....	2
FIELD INSPECTION RESULTS.....	2
PNRRA RIGHT-OF-WAY.....	2
CULVERT	2
CHANNEL.....	3
MASONRY RETAINING WALL ALONG S.R. 0611	3
RATINGS SUMMARY	4
MAINTENANCE RECOMMENDATIONS	5
MAINTENANCE RECOMMENDATIONS TO BE COORDINATED WITH PENNDOT DISTRICT 5-0.....	5
APPENDIX 1 – PHOTOGRAPHS	
APPENDIX 2 – LIVE LOAD RATING	

INTENTIONALLY BLANK

LOCATION MAP



Culvert Site:

Upper Mount Bethel Township
Northhampton County, PA
Latitude: $40^{\circ} 56' 50.0''$
Longitude: $-75^{\circ} 6' 50.9''$

Map Obtained From:
Northhampton County
Type 10 General Highway Map

INTENTIONALLY BLANK

GENERAL INFORMATION

BRIDGE DESCRIPTION

Year Built:	1909
Rehabilitation Year:	N/A
Structure Type:	Twin Cell Cast-In-Place Reinforced Concrete Rigid Frame
Structure Length:	30'-6" (Two 14'-0" Spans)
Number of Spans:	2
Deck type:	N/A - Culvert Under Fill
Culvert Length:	59.3' (Out-to-Out, Railroad Section)
Underclearance:	9'-0" (Upstream Fascia) 10'-6" (Downstream Fascia)

FIELD INSPECTION RESULTS

PNRRA RIGHT-OF-WAY

The PNRRA right-of-way on top of the culvert and in approach of the culvert is heavily vegetated and overgrown with tree growth (See Photos 3 to 5).

CULVERT

The cast-in-place concrete twin cell culvert is comprised of (2) distinct sections. The PNRRA culvert section was built in 1909 for railroad traffic and is in fair condition overall (See Photos 1 and 6 to 13). The PennDOT culvert section was added in 1936 to support SR 0611 over Slateford Creek and is in poor condition overall (See Photos 2, 14, and 15). The below observations primarily concentrate on the downstream PNRRA section:

Top Slab:

The top slab has an area of fine map cracking with efflorescence and stalactites along the downstream end of both Spans 1 & 2 (See Photos 22 & 23). A few top slab construction joints along the culvert exhibit efflorescence with stalactites, active water seepage, and areas of scale.

The PennDOT extension section has failing drainage structures with unreinforced soil and loose rocks noted above the top slab of both culvert spans at the construction joint with the PNRRA section (See Photos 18 and 19). Both drainage inlets exhibit areas of severe scale and spalling concrete surrounding the opening with several exposed longitudinal and transverse reinforcing steel bars exhibiting severe corrosion and section loss (25% to 75% estimated section remaining). Both inlets are located

at the toe of the steep slope along the east side of SR 0611 and are partially covered with debris and railroad ties.

Sidewalls:

The cast-in-place reinforced concrete sidewalls of the PNRRA section exhibit areas of hairline to fine map cracking with some efflorescence and associated concrete delamination along the downstream ends of both spans. The walls also have areas of scale and shallow spalling along the haunches and adjacent to a few construction joints with some light water seepage (See Photos 20 and 21). The base of all walls exhibits a band of concrete scaling and abrasion with the worst area at the downstream end of the middle wall (1'-6" high by 6" deep).

Floor:

The cast-in-place concrete floor of the PNRRA section exhibits heavy concrete scale with exposed aggregate and a few 1/8" to 1/4" wide cracks. A 1'-0" diameter by 6" deep spall is located at mid length of Span 1 in the PNRRA section.

Headwall:

The cast-in-place reinforced concrete headwall in the PNRRA section (downstream) exhibits several fine to 1/16" wide horizontal and scattered hairline cracks with light efflorescence.

The previously failed cast-in-place reinforced concrete headwall in the PennDOT section (upstream) has been replaced with gabion baskets (See Photo 2).

Wingwalls:

The northeast and northwest (downstream) non-integral cast-in-place reinforced concrete wingwalls in the PNRRA section exhibit a few fine scattered cracks with efflorescence.

The southwest (upstream) cast-in-place reinforced concrete integral wingwall in the PennDOT section exhibits severe scale along the interface with the culvert up to 12" deep and leans 7 1/4" toward the stream. This lean has been monitored on a 6-month inspection frequency since 2013 (See Photo 28).

CHANNEL

The channel flows from west to east with fair to poor alignment (See Photos 14 to 17). A large pile of debris directs flow primarily through Span 1 with minor scour along the inlet (See Photo 2). Heavy scour at the outlet undermines the cast-in-place concrete apron up to 1'-0" high and 1'-0" deep (See Photo 27). The stream banks are steep and heavily vegetated with rip rap protection lining the downstream channel.

MASONRY RETAINING WALL ALONG S.R. 0611

The masonry retaining wall along S.R. 0611 was constructed to support the steep slopes from the edge of the roadway down to the PNRRA right-of-way approximately 1/2 mile south of the Slateford Creek culvert. The overall length of the masonry retaining wall is approximately 950'-0" long and was constructed in (3) distinct

sections. The PennDOT as-built plans from 1936 denote that a 500'-0" masonry retaining wall was constructed along S.R. 0611 in this area. The northernmost section of the wall is round stacked stone, 3'-0" to 4'-0" high, and approximately 200'-0" long (See Photo 29). This section of the retaining wall is in fair condition overall and requires approximately 50 SF of reconstruction. The middle section of the wall is a stone masonry wall, 4'-0" to 7'-3" high, and is approximately 500'-0" long (See Photo 30). This section of the retaining wall is in satisfactory condition overall and requires approximately 200 LF to 300 LF of repointing. The southernmost section of the wall is stacked stone, 3'-0" to 4'-0" high, and approximately 250'-0" long (See Photo 31). This section of the retaining wall is in satisfactory condition overall and requires approximately 50 SF of reconstruction.

RATINGS SUMMARY

A rating analysis was performed for the Cooper E80 rail loading and provided in Appendix 2. As no records for the as-built condition of PNRRA culvert section were found, assumptions were made including but not limited to:

- PennDOT's BXLRFD program was used to rate the culvert using LRFD method.
- The PNRRA culvert section has the same reinforcing and dimensions as the PennDOT culvert section.
- The earth cover was assumed to be 2'-4" over the entire culvert.
- The structure was analyzed as a rigid frame on spread footings.
- The Cooper E80 live load was inputted as a Special Live Load.

The analysis showed an Inventory Rating (IR) of 0.61 and an Operating Rating (OP) of 0.79 for the PNRRA culvert.

MAINTENANCE RECOMMENDATIONS

PNRRA Culvert Critical, High Priority, & Priority Maintenance

- Clean and repair the heavily deteriorated top slab concrete adjacent to the drainage inlets in both spans at the construction joint between the PNRRA and PennDOT culvert sections: 2 SY @ \$5,900.00
- Fill in the 3'-0" deep scour hole just downstream of the PNRRA culvert section apron that is undermining the apron: 10 CY @ \$7,500.00

PNRRA Culvert Recommended Maintenance Items

- Repair the scaling concrete along the waterline throughout the PNRRA culvert section: 4 CY @ \$11,500.00
- Repair the delaminated and cracked concrete at the construction joints and along the east fascia walls and top slab of the PNRRA culvert section: 25 SY @ \$73,200.00
- Repave the heavily scaled concrete floor throughout both spans in the PNRRA culvert section: 185 SY @ \$28,900.00

Total Repair Cost of Recommended Maintenance: \$127,000.00

Note: Costs include a 25% contingency.

MAINTENANCE RECOMMENDATIONS TO BE COORDINATED WITH PENNDOT DISTRICT 5-0

Critical, High Priority, & Priority Maintenance

- Clear the drainage inlets and provide new drainage structures in both spans above the PennDOT culvert section at the construction joint with the PNRRA culvert section (2 Each).
- Clean and repair the heavily deteriorated top slab concrete adjacent to the drainage inlets in both spans at the construction joint between the PNRRA and PennDOT culvert sections (3 SY).

Culvert Recommended Maintenance Items

- Remove the heavy debris obstructing Span 2 just upstream of the PennDOT culvert section directing flow primarily through Span 1 (50 CY).

Masonry Retaining Wall Recommended Maintenance Items

- Reconstruct the missing and displaced stone along the northernmost section of the stacked stone retaining wall (50 SF).
- Repoint the loose and cracked mortar joints in the middle section of the stone masonry retaining wall (300 LF).

APPENDIX 1 – PHOTOGRAPHS



Photo 1 – Right (Downstream) elevation.



Photo 2 – Left (Upstream) elevation (PennDOT Section). Note the heavily deteriorated fascia with exposed and corroded reinforcement and a gabion basket headwall. Also, note the heavy debris accumulation obstructing Span 2.



Photo 3 – General view of the PNRRA right-of-way looking north from the culvert. Note the heavy tree and vegetation overgrowth.



Photo 4 – General view of the PNRRA right-of-way looking south from the culvert. Note the heavy tree and vegetation overgrowth.



Photo 5 – General view of top side from the northeast corner of the culvert looking southwest. Note the heavy tree and vegetation overgrowth.



Photo 6 – General underside view of Span 1 from the east fascia of the PNRRA section looking west.



Photo 7 – General underside view of Span 2 from the east fascia of the PNRRA section looking west.



Photo 8 – General view of the PNRRA south culvert wall in Span 1 looking southwest from the east facia.



Photo 9 – General view of the south face of the PNRRA middle culvert wall in Span 1 looking northwest from the east facia.



Photo 10 – General view of the north face of the PNRRA middle culvert wall in Span 2 looking southwest from the east facia.



Photo 11 – General view of the PNRRA north culvert wall in Span 2 looking northwest from the east facia.




Photo 12 – General view of the southeast wingwall at the outlet looking south. Note the heavy vegetation overgrowth.



Photo 13 – General view of the northeast wingwall at the outlet looking north. Note the heavy vegetation overgrowth.



Photo 14 – General upstream view of Span 1 of the PennDOT section from the construction joint looking west.



Photo 15 – General upstream view of Span 2 of the PennDOT section from the construction joint looking west.




Photo 16 – Waterway looking upstream from the west fascia.



Photo 17 – Waterway looking downstream from the east fascia.




Photo 18 – Heavily deteriorated drainage inlet through the top slab in Span 1 of the PennDOT section at the construction joint.




Photo 19 – Heavily deteriorated drainage inlet through the top slab in Span 2 of the PennDOT section at the construction joint.




Photo 20 – Span 1 south wall construction joint between the sections with active water seepage and efflorescence.




Photo 21 – Span 2 north wall construction joint between the sections with active water seepage and efflorescence.



Photo 22 – Close up view of the Span 1 east fascia and headwall. Note the heavy vegetation overgrowth and cracked concrete with efflorescence and stalactites in the top slab.



Photo 23 – Close up view of the Span 2 east fascia and headwall. Note the heavy vegetation overgrowth and cracked concrete with efflorescence and stalactites in the top slab.



Photo 24 – Abrasion and concrete scaling up to 1'-0" high and 3" deep along the waterline. Typical in both Spans.



Photo 25 – Abrasion and concrete scaling up to 1'-6" high and 4" deep along the middle culvert wall at the outlet.



Photo 26 – Heavy abrasion and concrete scaling along the concrete floor. Typical of both spans (Span 2 shown).



Photo 27 – The outlet apron is undermined up to 1'-0" deep by 1'-0" high in the 3'-0" deep scour hole just downstream.



Photo 28 – The southwest wingwall in the PennDOT section (upstream) exhibits severe scale along the interface with the culvert up to 12" deep and leans 7¼" toward the stream.



Photo 29 – The typical view of the round stacked stone retaining wall along S.R. 0611 (northernmost section).



Photo 30 – The typical view of the stone masonry retaining wall along S.R. 0611 (middle section).



Photo 29 – The typical view of the stacked stone retaining wall along S.R. 0611 (southernmost section).

INTENTIONALLY BLANK

APPENDIX 2 – LIVE LOAD RATING

Greenman-Pedersen, Inc.

52 Glenaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00

SHEET NO.	OF		
CALCULATED BY:	AJK	DATE	6/21/19
CHECKED BY:	HF	DATE	7/1/19
Precast Reinforced Concrete Box Culvert			

Loading Computations**Barrier Dead Load**

Barrier Type	Headwall	
Additional Headwall Height	2	ft
Barrier Width	1	ft
Distribution Width	2	ft
Barrier Unit Weight	0.3	klf
Additional Headwall Weight	0.300	klf
Total Barrier Weight	0.600	klf
Barrier Dead Load	0.300	klf

(Enter Total Headwall Height if Barrier Type is a Headwall)

(Enter Headwall Width if Barrier Type is a Headwall)

Assumed

(2*Barrier Width)

1'-6" W X (Headwall Ht) X 0.150 klf

(Total Barrier Weight)

(Distribution Width)

Left Approach Slab Dead Load

Appr. Slab Width		ft
Appr. Slab Length		ft
Appr. Slab Thick.		ft
Culvert Length		ft
Appr. Slab Wt.	0	kips
Distribution Factor	0.5	

(Appr. Slab Width) X (Appr. Slab Length) X (Appr. Slab Thick.) X 0.150 kcf
 $\frac{1}{2}$ of DL to Culvert wall & $\frac{1}{2}$ of DL to Sleeper Slab**Approach Slab DL Left Wall**

Approach Slab DL Left Wall		kips
----------------------------	--	------

(Appr. Slab Wt.) X (Distribution Factor)
(Culvert Length)**Left Approach Slab Live Load**

Roadway Width		ft
No. of Lanes Loaded	0	
Multiple Presence Factor		
Approach Slab Length		ft
PHL-93 Lane Load	0.64	kips
Total Live Load		kips
Distribution Factor	0.5	
Culvert Length		ft

AASHTO 3.6.1.1.1
AASHTO 3.6.1.1.2

AASHTO 3.6.1.2.4

1/2 of LL to Culvert wall & 1/2 of LL to Sleeper Slab

Approach Slab LL Left Wall

Approach Slab LL Left Wall		kips
----------------------------	--	------

(Total Live Load) X (Distribution Factor)
(Culvert Length)**Right Approach Slab Dead Load**

Appr. Slab Width		ft
Appr. Slab Length		ft
Appr. Slab Thick.		ft
Culvert Length		ft
Appr. Slab Wt.	0	kips
Distribution Factor	0.5	

(Appr. Slab Width) X (Appr. Slab Length) X (Appr. Slab Thick.) X 0.150 kcf
 $\frac{1}{2}$ of DL to Culvert wall & $\frac{1}{2}$ of DL to Sleeper Slab**Approach Slab DL Right Wall**

Approach Slab DL Right Wall		kips
-----------------------------	--	------

(Appr. Slab Wt.) X (Distribution Factor)
(Culvert Length)

Greenman-Pedersen, Inc.

52 Glenaura National Blvd, Suite 302
Scranton, PA 18505
(570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00

SHEET NO.	OF
CALCULATED BY:	AJK
CHECKED BY:	HF
DATE	6/21/19
DATE	7/1/19

Precast Reinforced Concrete Box Culvert

Right Approach Slab Live Load

Roadway Width		ft
No. of Lanes Loaded	0	
Multiple Presence Factor		
Approach Slab Length		ft
PHL-93 Lane Load	0.64	klf
Total Live Load		kips
Distribution Factor	0.5	
Culvert Length		ft
Approach Slab LL Right Wall		klf

AASHTO 3.6.1.1.1

AASHTO 3.6.1.1.2

AASHTO 3.6.1.2.4

1/2 of LL to Culvert wall & 1/2 of LL to Sleeper Slab

(Total Live Load) X (Distribution Factor)
(Culvert Length)

Greenman-Pedersen, Inc.
 52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB:	SCR-2019407.00		
SHEET NO.	OF		
CALCULATED BY:	AJK	DATE	6/24/19
CHECKED BY:	HF	DATE	7/1/19
Precast Reinforced Concrete Box Culvert			

BXLRFD Assumptions

- LL Rating based on LRFD method
- Dimensions match PennDOT section (other than not having a bottom haunch) and supplemented by inspection report field measurements
- Reinforcement matches PennDOT section
- Analyze structure as a rigid frame (as there are no haunches present, which doesn't match the other structure, and the opening height changes)
- Cooper E80 trailing load neglected
- Historic Values for Reinforcement and Concrete Strength (1909)
- Fill height set to 2'-4" (minimum) from inspection
- Footing dimensions assumed
- Loads assumed not transferred as per DM-4 3.6.1.5.2P

BXLRFD Analysis Run Inputs

CTL	System of Units	US	Default Value
	Structure Type	2	1 - Single Celled Culvert, 2 - Twin Celled Culvert, U - U-channel
	Type of Run	AR	See BXLRFD Commentary
	Precast or CIP	C	
	Bottom Slab	N	
	Top Slab Support	M	M - Top slab is monolithic with walls, S - Top slab is simply supported on walls
	Frame Support	F	Leave Blank for Culverts with Bottom Slab
MAT	f'c for All Members	3	ksi Historic Concrete Strength (1909)
	f'c for Top Slab		ksi Leave Blank to use f'c for All Members, or Enter f'c for Top Slab for CIP Culverts
	Reinforcement Grade	33	ksi Historic Rebar Strength (1909)
	Reinforcement Type	B	W-Wire Mesh, B-Bars
	Alpha	45	Leave blank for no shear reinforcement.
	Rebar Size or Wire Dia.		Leave blank for analysis run.
	Epoxy Coated Bars	N	As per existing Plans
	Concrete Unit Weight for DL		Default (150 pcf)
	Concrete Unit Weight for E		Default (145 pcf)
	Reinforcement Ultimate Strength	50	
DIM	Clear Span	14	ft
	Clear Height	10.5833	ft
	Top Slab Thickness	24	in Enter Thickness for Analysis
	Bottom Slab Thickness	26	in Enter Thickness for Analysis
	Left Wall Thickness	15	in Enter Thickness for Analysis
	Right Wall Thickness	15	in Enter Thickness for Analysis
	Interior Wall Thickness	30	in Enter Thickness for Analysis
	Fill Grade		%
	Top Slab Grade		%
	U-Channel Left Wall Ht.		ft Enter Ht. for Analysis
	U-Channel Right Wall Ht.		ft Enter Ht. for Analysis
FTG	Left Footing Length	66	ft
	Left Footing Thk.	24	ft
	Left Toe Projection	24	ft
	Left Footing Length	66	ft
	Left Footing Thk.	24	ft
	Left Toe Projection	24	ft
	Interior Footing Width	78	ft
	Interior Footing Thk.	24	ft

Greenman-Pedersen, Inc.
 52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB:	SCR-2019407.00		
SHEET NO.	OF		
CALCULATED BY:	AJK	DATE	6/24/19
CHECKED BY:	HF	DATE	7/1/19
Precast Reinforced Concrete Box Culvert			

LDC			
Earth Weight Density	pcf	Default	
Height of Fill	ft	Set to 2'-4" min. from inspection	
No. of Lanes	--	AASHTO 3.6.1.1.1 (Roadway Width/12)	
LL Surcharge	ft	Default	
Live Load	E	E - Special Live Load	
Overlay Weight Density	pcf	Default	
Overlay Thickness	in		
Future Wearing Surface	psf	30 psf for Culverts at Grade, 0 otherwise	
Max. LL Distribution Length	ft		
Segment Length	ft	Use 165'/2 (Structure length from inspection report)	
Multiple Presence Factor		Default, Leave "Blank" no longer used.	
PA Traffic Factor		Default, Leave "Blank" no longer used.	
Fatigue Dynamic Load Allow.		Default, Leave "Blank" no longer used.	
Ductility Factor	--	Default, As per DM-4 Section 1.3.4, a factor other than 1.0 is not permitted	
Redundancy Factor	--	Default, As per DM-4 Section 1.3.4, a factor other than 1.0 is not permitted	
Importance Factor	--	Default, As per DM-4 Section 1.3.4, a factor other than 1.0 is not permitted	
P-82 Max. Dynamic Load Allow.	--	Default, 1.2 per DM-4 Section 3.6.2	
LL Override	--	Default	
Min. Equiv. Fluid Pressure	pcf	Default, As per DM-4 Table 3.11.5.5-2P	
Max. Equiv. Fluid Pressure	pcf	Default, As per DM-4 Table 3.11.5.5-2P	
Barrier Dead Load	klf	See Loading Computations	
Approach Slab DL Left Wall	klf	See Loading Computations	
Approach Slab LL Left Wall	klf	See Loading Computations	
Approach Slab DL Right Wall	klf	See Loading Computations	
Approach Slab LL Right Wall	klf	See Loading Computations	
Ratings without FWS	Y	Y-For Analysis Runs	
Backfill Type		Default (O -Other Backfill Type)	
Number of Precast Shear		Number of Precast Segements With Shear Transfer	
SLL			
Gage Distance	4.7083	ft	
Passing Distance	0	ft	
Axle Effect	N		
Lane Load	0	klf	
Percent Increase	0		
Load Factor; STR I	1.75		
Load Factor; STR II	1.35		
Load Factor; SERV I	1		
Load Factor Fatigue	1.75		
SAL			
Axle Load	40	kips	
Axle Spacing	8	ft	
Axle Load	80	kips	
Axle Spacing	5	ft	
Axle Load	80	kips	
Axle Spacing	5	ft	
Axle Load	80	kips	
Axle Spacing	5	ft	
Axle Load	80	kips	
Axle Spacing	9	ft	
Axle Load	52	kips	
Axle Spacing	5	ft	
Axle Load	52	kips	
Axle Spacing	6	ft	

Greenman-Pedersen, Inc.

52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB:	SCR-2019407.00		
SHEET NO.	OF		
CALCULATED BY:	AJK	DATE	6/24/19
CHECKED BY:	HF	DATE	7/1/19
Precast Reinforced Concrete Box Culvert			

Axle Load

52

 kips
 Axle Spacing

5

 ft

Axle Load

52

 kips
 Axle Spacing

8

 ft

Axle Load

40

 kips
 Axle Spacing

8

 ft

Axle Load

80

 kips
 Axle Spacing

5

 ft

Axle Load

80

 kips
 Axle Spacing

5

 ft

Axle Load

80

 kips
 Axle Spacing

5

 ft

Axle Load

80

 kips
 Axle Spacing

9

 ft

Axle Load

52

 kips
 Axle Spacing

5

 ft

Axle Load

52

 kips
 Axle Spacing

6

 ft

Axle Load

52

 kips
 Axle Spacing

5

 ft

Axle Load

52

 kips
 Axle Spacing

ft

HCH

Top Left X	18	in
Top Left Y	18	in
Top Right X	18	in
Top Right Y	18	in
Bot Left X		in
Bot Left Y		in
Bot Right X		in
Bot Right Y		in
Top Int X	18	in
Top Int Y	18	in
Bot Int X		in
Bot Int Y		in

Leave Blank for Single Cell Culverts
 Leave Blank for Single Cell Culverts

CVR

Top Slab Top Cover	1.875	in	Default
Top Slab Bottom Cover	2	in	Default
Bottom Slab Top Cover	2	in	Default
Bottom Slab Bot Cover	1.875	in	Default
All Wall Covers	2.25	in	Default
Footing Top Cover		in	Default
Footing Bot Cover		in	Default

Greenman-Pedersen, Inc.

52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00
 SHEET NO. OF
 CALCULATED BY: AJK DATE 6/24/19
 CHECKED BY: HF DATE 7/1/19
 Precast Reinforced Concrete Box Culvert

TSR

Slab No.	1
Face	T
Range Distance	14 ft
Reinf. Size or Wire Dia.	10
[2] Spacing	12 in
Range Distance	ft
Reinf. Size or Wire Dia.	
[3] Spacing	in
Range Distance	ft
Reinf. Size or Wire Dia.	
Spacing	in

Slab No.	2
Face	T
Range Distance	14 ft
Reinf. Size or Wire Dia.	10
[2] Spacing	12 in
Range Distance	ft
Reinf. Size or Wire Dia.	
[3] Spacing	in
Range Distance	ft
Reinf. Size or Wire Dia.	
Spacing	in

Slab No.	1
Face	B
Range Distance	14 ft
Reinf. Size or Wire Dia.	8
[2] Spacing	12 in
Range Distance	ft
Reinf. Size or Wire Dia.	
[3] Spacing	in
Range Distance	ft
Reinf. Size or Wire Dia.	
Spacing	in

Slab No.	2
Face	B
Range Distance	14 ft
Reinf. Size or Wire Dia.	8
[2] Spacing	12 in
Range Distance	ft
Reinf. Size or Wire Dia.	
[3] Spacing	in
Range Distance	ft
Reinf. Size or Wire Dia.	
Spacing	in

BSR

Slab No.	1
Face	T
Range Distance	14 ft
Reinf. Size or Wire Dia.	8
[2] Spacing	12 in
Range Distance	ft
Reinf. Size or Wire Dia.	
[3] Spacing	in
Range Distance	ft
Reinf. Size or Wire Dia.	
Spacing	in

Greenman-Pedersen, Inc.

52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00
 SHEET NO. OF
 CALCULATED BY: AJK DATE 6/24/19
 CHECKED BY: HF DATE 7/1/19
 Precast Reinforced Concrete Box Culvert

Slab No.	2	
Face	T	
Range Distance	14	ft
Reinf. Size or Wire Dia.	8	
[2] Spacing	12	in
Range Distance		ft
Reinf. Size or Wire Dia.		
[3] Spacing		in
Range Distance		ft
Reinf. Size or Wire Dia.		
Spacing		in

Slab No.	1	
Face	B	
Range Distance	14	ft
Reinf. Size or Wire Dia.	10	
[2] Spacing	12	in
Range Distance		ft
Reinf. Size or Wire Dia.		
[3] Spacing		in
Range Distance		ft
Reinf. Size or Wire Dia.		
Spacing		in

Slab No.	2	
Face	B	
Range Distance	14	ft
Reinf. Size or Wire Dia.	10	
[2] Spacing	12	in
Range Distance		ft
Reinf. Size or Wire Dia.		
[3] Spacing		in
Range Distance		ft
Reinf. Size or Wire Dia.		
Spacing		in

WLR

Wall No.	1	
Face	L	
Range Distance	10	ft
Reinf. Size or Wire Dia.	8	
[2] Spacing	12	in
Range Distance		ft
Reinf. Size or Wire Dia.		
[3] Spacing		in
Range Distance		ft
Reinf. Size or Wire Dia.		
Spacing		in

Wall No.	1	
Face	R	
Range Distance	10	ft
Reinf. Size or Wire Dia.	4	
[2] Spacing	12	in
Range Distance		ft
Reinf. Size or Wire Dia.		
[3] Spacing		in
Range Distance		ft
Reinf. Size or Wire Dia.		
Spacing		in

Greenman-Pedersen, Inc.

52 Glenmaura National Blvd, Suite 302
Scranton, PA 18505
(570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00
SHEET NO. OF
CALCULATED BY: AJK DATE 6/24/19
CHECKED BY: HF DATE 7/1/19
Precast Reinforced Concrete Box Culvert

[2]	Wall No.	2
	Face	L
	Range Distance	10 ft
	Reinf. Size or Wire Dia.	4
	Spacing	12 in
[3]	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
[2]	Wall No.	2
	Face	R
	Range Distance	10 ft
	Reinf. Size or Wire Dia.	4
	Spacing	12 in
[3]	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
[2]	Wall No.	3
	Face	L
	Range Distance	10 ft
	Reinf. Size or Wire Dia.	4
	Spacing	12 in
[3]	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
[2]	Wall No.	3
	Face	R
	Range Distance	10 ft
	Reinf. Size or Wire Dia.	8
	Spacing	12 in
[3]	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in
	Range Distance	ft
	Reinf. Size or Wire Dia.	
	Spacing	in

Greenman-Pedersen, Inc.
 52 Glenmaura National Blvd, Suite 302
 Scranton, PA 18505
 (570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00
 SHEET NO. OF
 CALCULATED BY: AJK DATE 6/24/19
 CHECKED BY: HF DATE 7/1/19
 Precast Reinforced Concrete Box Culvert

FTR	
Footing Number	1
Face	T
Reinf Size or Wire Dia.	8
Spacing	12 in
Footing Number	1
Face	B
Reinf Size or Wire Dia.	10
Spacing	12 in
Footing Number	2
Face	T
Reinf Size or Wire Dia.	8
Spacing	12 in
Footing Number	2
Face	B
Reinf Size or Wire Dia.	10
Spacing	12 in
Footing Number	3
Face	T
Reinf Size or Wire Dia.	8
Spacing	12 in
Footing Number	3
Face	B
Reinf Size or Wire Dia.	10
Spacing	12 in

TVA	
Slab Number	1
Region Start Distance	1.25 ft
Region End Distance	1.25 ft
Shear Rein. Area	1.27 in^2
[2] Spacing	0 in
Region Start Distance	12.75 ft
Region End Distance	12.75 ft
Shear Rein. Area	1.27 in^2
Spacing	0 in
Slab Number	2
Region Start Distance	1.25 ft
Region End Distance	1.25 ft
Shear Rein. Area	1.27 in^2
[2] Spacing	0 in
Region Start Distance	12.75 ft
Region End Distance	12.75 ft
Shear Rein. Area	1.27 in^2
Spacing	0 in

BVA	
Slab Number	1
Region Start Distance	1.25 ft
Region End Distance	1.25 ft
Shear Rein. Area	1.27 in^2
[2] Spacing	0 in
Region Start Distance	12.75 ft
Region End Distance	12.75 ft
Shear Rein. Area	1.27 in^2
Spacing	0 in

Greenman-Pedersen, Inc.

52 Glenmaura National Blvd, Suite 302
Scranton, PA 18505
(570) 342-3700 FAX (570) 342-4080

JOB: SCR-2019407.00
SHEET NO. OF
CALCULATED BY: AJK DATE 6/24/19
CHECKED BY: HF DATE 7/1/19
Precast Reinforced Concrete Box Culvert

Slab Number	2
Region Start Distance	1.25 ft
Region End Distance	1.25 ft
Shear Rein. Area	1.27 in^2
Spacing	0 in

[2]

Region Start Distance	12.75 ft
Region End Distance	12.75 ft
Shear Rein. Area	1.27 in^2
Spacing	0

```
*****
*  
* Program Title      LRFD Box Culvert Design and Rating  
* Program Name       BXLRFD  
* Version           2.8.0.0  
* Last Updated      10/12/2018  
* Documentation     09/2018  
* License No.       333687  
*  
*****  
*  
* SLATEFORD PRELIMINARY CULVERT RATING  
* RIGID FRAME RUN  
* *****  
* DONE: AJK          DATE: 06/24/19  
* CHCK: HF           DATE: 07/01/19  
* *****  
*  
*****  
*  
* COPYRIGHT (C) 1997-2018  
* COMMONWEALTH OF PENNSYLVANIA  
* DEPARTMENT OF TRANSPORTATION  
*  
* ALL RIGHTS RESERVED  
*  
* DUPLICATION, ALTERATION, OR OTHER UNAUTHORIZED  
* USE OF THESE MATERIALS IS STRICTLY PROHIBITED.  
*  
*  
* THE COMMONWEALTH EXCLUDES ANY AND ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF  
* MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIMITS THE USER'S REMEDY  
* TO RETURN OF THE SOFTWARE AND DOCUMENTATION TO THE COMMONWEALTH FOR REPLACEMENT.  
*  
* THE COMMONWEALTH MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED,  
* WITH RESPECT TO THIS SOFTWARE OR ACCOMPANYING DOCUMENTATION, INCLUDING THEIR  
* QUALITY, PERFORMANCE, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. THIS  
* SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" AND THE USER ASSUMES THE ENTIRE RISK  
* AS TO THEIR QUALITY AND PERFORMANCE.  
*  
* THE COMMONWEALTH WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL,  
* OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE SOFTWARE OR  
* ANY ACCOMPANYING DOCUMENTATION.  
*
```

SLATEFORD PRELIMINARY CULVERT RATING
 SUMMARY OF INPUT FILE

COMMAND: CTL

SYSTEM OF UNITS	US
STRUCTURE TYPE	2
TYPE OF RUN	AR
PRECAST OR CAST-IN-PLACE	C
BOTTOM SLAB	N
TOP SLAB SUPPORT	M
FRAME SUPPORT	F

COMMAND: MAT

f'c FOR ALL MEMBERS	3 ksi
f'c FOR TOP SLAB AT GRADE	* ksi (computed, if necessary)
REINFORCEMENT GRADE	33 ksi
REINFORCEMENT TYPE	B
ALPHA	45 degrees
REBAR SIZE OR WIRE DIAM	* * (computed, if necessary)
EPOXY COATED	N
DENSITY OF CONC. FOR DL	150.0 lb/ft^3 (default)
DENSITY OF CONC. FOR E	145.0 lb/ft^3 (default)
REINF ULT TENS STRENGTH	50 ksi

COMMAND: DIM

CLEAR SPAN	14 ft
CLEAR HEIGHT	10.5833 ft
TOP SLAB THICKNESS	24 in
BOTTOM SLAB THICKNESS	26 in
LEFT WALL THICKNESS	15 in
RIGHT WALL THICKNESS	15 in
INTERIOR WALL THICKNESS	30 in
FILL GRADE	0.0 (default)
TOP SLAB GRADE	0.0 (default)
UCHNL LEFT WALL HEIGHT	* ft (computed, if necessary)
UCHNL RIGHT WALL HEIGHT	* ft (computed, if necessary)

COMMAND: FTG

LEFT FOOTING WIDTH	66 in
LEFT FOOTING THICKNESS	24 in
LEFT TOE PROJECTION	24 in
RIGHT FOOTING WIDTH	66 in
RIGHT FOOTING THICKNESS	24 in
RIGHT TOE PROJECTION	24 in
INTERIOR FTG WIDTH	78 in
INTERIOR FTG THICKNESS	24 in

COMMAND: LDC

EARTH WEIGHT/DENSITY	140.0 lbf/ft^3 (default)
HEIGHT OF FILL	2.3333 ft
NUMBER OF LANES	1
LIVE LOAD SURCHARGE	0 ft
LIVE LOAD	E
OVERLAY WEIGHT/DENSITY	150.0 lbf/ft^3 (default)
OVERLAY THICKNESS	0 in
FUTURE WEARING SURFACE	0 lbf/ft^2
LL DISTRIBUTION LENGTH	82.5 ft
SEGMENT LENGTH	82.5 ft
MULTIPLE PRESENCE REDUCT	1.0 (default)
PA TRAFFIC FACTOR	* (computed, if necessary)
FATIGUE DYN. LOAD ALLOW.	* (computed, if necessary)
DUCTILITY FACTOR	1.0 (default)
REDUNDANCY FACTOR	1.0 (default)
IMPORTANCE FACTOR	1.0 (default)
PERMIT DYN. LOAD ALLOW.	1.20 (default)
LIVE LOAD OVERRIDE	1
MIN EQUIV FLUID PRESS	45.0 lbf/ft^3 (default)
MAX EQUIV FLUID PRESS	70.0 lbf/ft^3 (default)
BARRIER DEAD LOAD	0.3 kip/ft
APPROACH SLAB DL-LEFT	0 kip (default)
APPROACH SLAB LL-LEFT	0 kip (default)
APPROACH SLAB DL-RIGHT	0 kip (default)
APPROACH SLAB LL-RIGHT	0 kip (default)
RATINGS W/O FWS	Y
BACKFILL TYPE	* (computed, if necessary)
NO. PC SHEAR TRNS SEG	2 (default)

SLATEFORD PRELIMINARY CULVERT RATING
SUMMARY OF INPUT FILE (cont.)

COMMAND: SLL

GAGE DISTANCE	4.7083 ft
PASSING DISTANCE	0 ft
AXLE EFFECT	N
LANE LOAD	0 Kip/ft
PERCENT INCREASE	0
LOAD FACTOR STRENGTH I	1.75
LOAD FACTOR STRENGTH II	1.35
LOAD FACTOR SERVICE I	1
LOAD FACTOR FATIGUE	1.75

COMMAND: SAL

AXLE LOAD	40 kip
AXLE SPACING	8 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	9 ft
AXLE LOAD	52 kip
AXLE SPACING	5 ft
AXLE LOAD	52 kip
AXLE SPACING	6 ft
AXLE LOAD	52 kip
AXLE SPACING	5 ft
AXLE LOAD	52 kip
AXLE SPACING	8 ft
AXLE LOAD	40 kip
AXLE SPACING	8 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	5 ft
AXLE LOAD	80 kip
AXLE SPACING	9 ft
AXLE LOAD	52 kip
AXLE SPACING	5 ft
AXLE LOAD	52 kip
AXLE SPACING	* ft (computed, if necessary)

COMMAND: HCH

TOP LEFT X	18 in
TOP LEFT Y	18 in
TOP RIGHT X	18 in
TOP RIGHT Y	18 in
BOTTOM LEFT X	* in (computed, if necessary)
BOTTOM LEFT Y	* in (computed, if necessary)
BOTTOM RIGHT X	* in (computed, if necessary)
BOTTOM RIGHT Y	* in (computed, if necessary)
TOP INTERIOR X	18 in
TOP INTERIOR Y	18 in
BOTTOM INTERIOR X	* in (computed, if necessary)
BOTTOM INTERIOR X	* in (computed, if necessary)

SLATEFORD PRELIMINARY CULVERT RATING
SUMMARY OF INPUT FILE (cont.)

COMMAND: CVR
TOP SLAB - TOP COVER 1.875 in
TOP SLAB - BOTTOM COVER 2 in
BOTTOM SLAB - TOP COVER 2 in
BOTTOM SLAB - BOTTOM CVR 1.875 in
ALL WALL COVERS 2.25 in
FOOTING - TOP COVER 2 in
FOOTING - BOTTOM COVER 3 in

COMMAND: TSR
SLAB NUMBER 1
FACE T
RANGE DISTANCE 14 ft
BAR SIZE OR WIRE DIAM 10 *
SPACING 12 in

COMMAND: TSR
SLAB NUMBER 2
FACE T
RANGE DISTANCE 14 ft
BAR SIZE OR WIRE DIAM 10 *
SPACING 12 in

COMMAND: TSR
SLAB NUMBER 1
FACE B
RANGE DISTANCE 14 ft
BAR SIZE OR WIRE DIAM 8 *
SPACING 12 in

COMMAND: TSR
SLAB NUMBER 2
FACE B
RANGE DISTANCE 14 ft
BAR SIZE OR WIRE DIAM 8 *
SPACING 12 in

COMMAND: WLR
WALL NUMBER 1
FACE L
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 8 *
SPACING 12 in

COMMAND: WLR
WALL NUMBER 1
FACE R
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 4 *
SPACING 12 in

COMMAND: WLR
WALL NUMBER 2
FACE L
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 4 *
SPACING 12 in

COMMAND: WLR
WALL NUMBER 2
FACE R
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 4 *
SPACING 12 in

SLATEFORD PRELIMINARY CULVERT RATING
SUMMARY OF INPUT FILE (cont.)

COMMAND: WLR
WALL NUMBER 3
FACE L
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 4 *
SPACING 12 in

COMMAND: WLR
WALL NUMBER 3
FACE R
RANGE DISTANCE 10.5833 ft
BAR SIZE/WIRE DIAM 8 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 1
FACE T
BAR SIZE OR WIRE DIAM 8 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 1
FACE B
BAR SIZE OR WIRE DIAM 10 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 2
FACE T
BAR SIZE OR WIRE DIAM 8 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 2
FACE B
BAR SIZE OR WIRE DIAM 10 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 3
FACE T
BAR SIZE OR WIRE DIAM 8 *
SPACING 12 in

COMMAND: FTR
FOOTING NUMBER 3
FACE B
BAR SIZE OR WIRE DIAM 10 *
SPACING 12 in

COMMAND: TVA
SLAB NUMBER 1
REGION START DISTANCE 1.25 ft
REGION END DISTANCE 1.25 ft
SHEAR REINFORCEMENT AREA 1.27 in^2
SPACING 0 in
REGION START DISTANCE 12.75 ft
REGION END DISTANCE 12.75 ft
SHEAR REINFORCEMENT AREA 1.27 in^2
SPACING 0 in

COMMAND: TVA
SLAB NUMBER 2
REGION START DISTANCE 1.25 ft
REGION END DISTANCE 1.25 ft
SHEAR REINFORCEMENT AREA 1.27 in^2
SPACING 0 in
REGION START DISTANCE 12.75 ft
REGION END DISTANCE 12.75 ft
SHEAR REINFORCEMENT AREA 1.27 in^2
SPACING 0 in

SLATEFORD PRELIMINARY CULVERT RATING
SUMMARY OF INPUT FILE (cont.)

COMMAND: OIN
INPUT FILE ECHO 0
INPUT COMMANDS 1
INPUT SUMMARY 0

COMMAND: OUR
SECTION PROPERTIES * (computed, if necessary)
LIVE LOAD RATING 1
RATING SUMMARY 1
DL EFFECTS & CAPACITIES * (computed, if necessary)
FLEXURAL REINFORCEMENT * (computed, if necessary)
SHEAR DESIGN * (computed, if necessary)
FOUNDATION PRESSURE 0 (default)
QUANTITIES * (computed, if necessary)
SERVICEABILITY TABLE * (computed, if necessary)
SERVICEABILITY SUMMARY 1 (default)
FOUNDATION PRESS SUMMARY 1 (default)
MIN. REINFORCEMENT CHECK 1 (default)
%WARNING - <Bar and wire clear covers>:
Top slab, top cover less than lower limit.
Verify input on the CVR card.
%WARNING - <Inconsistent Data>:
The Fatigue limit state is no longer
analyzed by the program.
Load Factor for Fatigue will be ignored.
Please verify input on the SLL card.

Note: Wall distances begin at the bottom of the wall and slab distances
begin at the left side of the slab.

SLATEFORD PRELIMINARY CULVERT RATING
ADDITIONAL INFORMATION

COMPUTED VALUES

Input	Computed Flexure	Computed Axial	Computed Shear	Computed Development
Reinf	Reinf	Reinf	Reinf	Reinf
Grade	Grade	Grade	Grade	Grade
(ksi)	(ksi)	(ksi)	(ksi)	(ksi)
33.000	33.000	33.000	33.000	33.000

ADDITIONAL GEOMETRY

Final Component Thickness

Top Slab #1 : 24.00 in
Top Slab #2 : 24.00 in
Wall #1 : 15.00 in
Wall #2 : 30.00 in
Wall #3 : 15.00 in

Final Strip Footing Projections

Left Wall Toe Projection : 24.00 in
Left Wall Heel Projection : 27.00 in
Center Wall Projection : 24.00 in
Right Wall Toe Projection : 24.00 in
Right Wall Heel Projection : 27.00 in

SLATEFORD PRELIMINARY CULVERT RATING
LIVE LOAD ELAT & IM TABLE

Dynamic Load Allowance

Fill Height (ft)	IM	Permit IM
2.33	1.28	N/A

Case 1 - On Deck Loading

No. of Lanes Loaded	c-c Culvert Span (ft)	MPF *	Calc Elat (ft)	-----	Calc Elat MPF (ft)	Seg Length (ft)	Elat Used (ft)
1	15.88	1.20	9.90		8.25	82.5	8.25

Case 2 - Thru Fill Loading

No. of Lanes Loaded	Fill Height (ft)	LL Distribution Length (ft)	MPF *	Total Width (LANE(i)) (ft)	Elat Used (ft)
1	2.33	82.5	1.20	11.56	9.63

* Includes Multiple Presence Reduction Factor

SLATEFORD PRELIMINARY CULVERT RATING
SERVICEABILITY SPACING SUMMARY

Location	Minimum Primary Spacing	Maximum Primary Spacing	Temp/ Shrink Spacing	Crack Control Spacing
Top Slab No. 1	OK	OK	OK	OK
Top Slab No. 2	OK	OK	OK	OK
Wall No. 1	OK	OK	OK	OK
Wall No. 2	OK	OK	OK	OK
Wall No. 3	OK	OK	OK	OK
STRIP FOOTING: Wall No. 1	OK	OK	OK	OK
STRIP FOOTING: Wall No. 2	OK	OK	OK	OK
STRIP FOOTING: Wall No. 3	OK	OK	OK	OK

SLATEFORD PRELIMINARY CULVERT RATING
 LIVE LOAD RATING W/O FWS

SPECIAL Loading: Top Slab No. 1

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft) (kips)	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
						IR STR-I	OR STR-II			
1.50	DL+E	2.84	1.90	46.05 F1	TN	2.22		0.79 B	0.57	0.90
	LL+I	19.45	2.36							
	DL+E	2.84	1.90	46.05 F1	TN		2.88	0.79 B	0.57	0.90
	LL+I	15.00	1.82							
2.80	DL+E	8.21	1.90	44.36 F1	TN	1.07		0.79 B	0.81 **	0.90
	LL+I	33.81	2.56							
	DL+E	8.21	1.90	44.36 F1	TN		1.39	0.79 B	0.81 **	0.90
	LL+I	26.08	1.98							
3.29	DL+E	9.72	1.90	-3.73	44.82 F1	TN	0.93		0.79 B	0.81 ** 0.90
	LL+I	37.74	3.68	-12.97	-28.60 V6		1.91	0.00		
	DL+E	9.72	1.90	-3.73	44.82 F1	TN		0.79 B	0.81 ** 0.90	
	LL+I	29.11	2.84	-10.00	-28.68 V6		2.47	0.00		
4.20	DL+E	11.76	1.90	-2.65	44.42 F1	TN	0.73		0.79 B	0.81 ** 0.90
	LL+I	44.98	3.90	-10.19	-27.60 V6		2.45	0.00		
	DL+E	11.76	1.90	-2.65	44.42 F1	TN		0.79 B	0.81 ** 0.90	
	LL+I	34.70	3.01	-7.86	-27.60 V6		3.17	0.00		
5.60	DL+E	13.00	1.90	-0.06	44.12 F1	TN	0.61		0.79 B	0.81 ** 0.90
	LL+I	51.17	3.93	7.27	26.67 V5		3.72	0.00		
	DL+E	13.00	1.90	-0.06	44.12 F1	TN		0.79 B	0.81 ** 0.90	
	LL+I	39.48	3.03	5.61	26.58 V5		4.82	0.00		
7.00	DL+E	11.92	1.90	1.60	44.25 F1	TN	0.65		0.79 B	0.81 ** 0.90
	LL+I	50.09	4.01	10.86	27.46 V5		2.40	0.00		
	DL+E	11.92	1.90	1.60	44.25 F1	TN		0.79 B	0.81 ** 0.90	
	LL+I	38.64	3.09	8.38	27.37 V5		3.11	0.00		
8.40	DL+E	8.53	1.90	3.25	44.87 F1	TN	0.89		0.79 B	0.81 ** 0.90
	LL+I	41.05	3.94	14.99	28.77 V5		1.70	0.00		
	DL+E	8.53	1.90	3.25	44.87 F1	TN		1.15	0.79 B	0.81 ** 0.90
	LL+I	31.66	3.04	11.56	28.77 V5		2.21	0.00		
9.80	DL+E	3.54	5.24	4.90	49.76 F1	TN	1.90		0.79 B	0.71 0.90
	LL+I	24.33	3.88	19.11	28.77 V5		1.25	0.00		
	DL+E	3.54	5.24	4.90	49.76 F1	TN		2.46	0.79 B	0.71 0.90
	LL+I	18.77	2.99	14.74	28.77 V5		1.62	0.00		
10.71	DL+E	-2.12	1.90	5.98	-67.84 F2	TN	2.94		1.27 T	0.62 0.90
	LL+I	-22.36	0.62	21.90	30.63 V5		1.13	0.00		
	DL+E	-2.12	1.90	5.98	-67.84 F2	TN		3.81	1.27 T	0.62 0.90
	LL+I	-17.25	0.48	16.90	30.63 V5		1.46	0.00		
11.20	DL+E	-5.20	1.90		-67.64 F2	TN	2.20		1.27 T	0.81 0.90
	LL+I	-28.41	0.69							
	DL+E	-5.20	1.90		-67.64 F2	TN		2.85	1.27 T	0.81 0.90
	LL+I	-21.92	0.53							
12.50	DL+E	-14.72	1.90		-67.21 F2	TN	1.13		1.27 T	0.81 0.90
	LL+I	-46.59	0.76							
	DL+E	-14.72	1.90		-67.21 F2	TN		1.46	1.27 T	0.81 0.90
	LL+I	-35.94	0.59							

SPECIAL Loading: Top Slab No. 2

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft) (kips)	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
						IR STR-I	OR STR-II			
1.50	DL+E	-14.72	1.90		-67.21 F2	TN	1.13		1.27 T	0.81 0.90
	LL+I	-46.58	0.76							
	DL+E	-14.72	1.90		-67.21 F2	TN		1.46	1.27 T	0.81 0.90
	LL+I	-35.94	0.58							
2.80	DL+E	-5.20	1.90		-67.63 F2	TN	2.20		1.27 T	0.81 0.90
	LL+I	-28.41	0.68					2.85	1.27 T	0.81 0.90
	DL+E	-5.20	1.90		-67.63 F2	TN			1.27 T	0.81 0.90
	LL+I	-21.92	0.52							
3.29	DL+E	-2.12	1.90	-5.98	-67.82 F2	TN	2.94		1.27 T	0.62 0.90
	LL+I	-22.36	0.61	-22.04	-30.63 V6		1.12	0.00		
	DL+E	-2.12	1.90	-5.98	-67.82 F2	TN		3.81	1.27 T	0.62 0.90
	LL+I	-17.25	0.47	-17.00	-30.63 V6		1.45	0.00		
4.20	DL+E	3.54	5.24	-4.90	49.77 F1	TN	1.90		0.79 B	0.71 0.90
	LL+I	24.33	3.88	-19.20	-28.77 V6		1.24	0.00		
	DL+E	3.54	5.24	-4.90	49.77 F1	TN		2.46	0.79 B	0.71 0.90
	LL+I	18.77	2.99	-14.82	-28.77 V6		1.61	0.00		

SLATEFORD PRELIMINARY CULVERT RATING
 LIVE LOAD RATING W/O FWS (cont.)

SPECIAL Loading: Top Slab No. 2 (cont.)

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft)	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
						IR STR-I	OR STR-II			
5.60	DL+E	8.53	1.90	-3.25	44.87 F1	TN	0.89	0.79 B	0.81 **	0.90
	LL+I	41.04	3.95	-14.83	-28.77 V6		1.72	0.00		
	DL+E	8.53	1.90	-3.25	44.87 F1	TN		0.79 B	0.81 **	0.90
	LL+I	31.66	3.05	-11.44	-28.77 V6			0.00		
7.00	DL+E	11.92	1.90	-1.60	44.25 F1	TN	0.65	0.79 B	0.81 **	0.90
	LL+I	50.10	4.00	-10.94	-27.48 V6		2.39	0.00		
	DL+E	11.92	1.90	-1.60	44.25 F1	TN		0.79 B	0.81 **	0.90
	LL+I	38.65	3.09	-8.44	-27.39 V6			0.00		
8.40	DL+E	13.00	1.90	0.06	44.11 F1	TN	0.61	0.79 B	0.81 **	0.90
	LL+I	51.17	3.92	-7.09	-26.66 V6		3.82	0.00		
	DL+E	13.00	1.90	0.06	44.11 F1	TN		0.79 B	0.81 **	0.90
	LL+I	39.48	3.02	-5.47	-26.57 V6			0.00		
9.80	DL+E	11.76	1.90	2.65	44.42 F1	TN	0.73	0.79 B	0.81 **	0.90
	LL+I	44.98	3.90	10.18	27.61 V5		2.45	0.00		
	DL+E	11.76	1.90	2.65	44.42 F1	TN		0.79 B	0.81 **	0.90
	LL+I	34.70	3.01	7.85	27.61 V5			0.00		
10.71	DL+E	9.72	1.90	3.73	44.83 F1	TN	0.93	0.79 B	0.81 **	0.90
	LL+I	37.74	3.69	12.93	28.60 V5		1.91	0.00		
	DL+E	9.72	1.90	3.73	44.83 F1	TN		0.79 B	0.81 **	0.90
	LL+I	29.11	2.85	9.97	28.67 V5			2.48	0.00	
11.20	DL+E	8.21	1.90		44.38 F1	TN	1.07	0.79 B	0.81 **	0.90
	LL+I	33.82	2.59							
	DL+E	8.21	1.90		44.38 F1	TN		1.39	0.79 B	0.81 ** 0.90
	LL+I	26.09	2.00							
12.50	DL+E	2.84	1.90		46.11 F1	TN	2.23		0.79 B	0.57 0.90
	LL+I	19.44	2.39							
	DL+E	2.84	1.90		46.11 F1	TN		2.89	0.79 B	0.57 0.90
	LL+I	15.00	1.85							

SPECIAL Loading: Wall No. 1

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft)	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
						IR STR-I	OR STR-II			
0.00	DL+E	-0.36	10.12		53.04 F1	TR	4.05	0.20 R	0.54 **	0.90
	LL+I	13.17	24.26							
	DL+E	-0.36	10.12		53.04 F1	TR		5.25	0.20 R	0.54 ** 0.90
	LL+I	10.16	18.72							
1.06	DL+E	0.00	10.58	-0.93	48.86 F4	CM	5.60		0.20 R	0.43 ** 0.90
	LL+I	8.73	27.29	4.03	13.84 V5		3.67	0.00		
	DL+E	0.00	10.58	-0.93	48.86 F4	CM		7.25	0.20 R	0.43 ** 0.90
	LL+I	6.74	21.05	3.11	13.84 V5			4.75	0.00	
2.12	DL+E	2.79	10.33	-0.36	36.32 F4	CM	7.35		0.20 R	0.33 ** 0.90
	LL+I	4.56	27.29	4.03	13.84 V5		3.52	0.00		
	DL+E	2.79	10.33	-0.36	36.32 F4	CM		9.53	0.20 R	0.33 ** 0.90
	LL+I	3.52	21.05	3.11	13.84 V5			4.57	0.00	
3.17	DL+E	4.22	10.09	0.17	8.11 F4	CM	9.86		0.20 R	0.27 ** 0.90
	LL+I	0.39	27.29	4.03	13.84 V5		3.39	0.00		
	DL+E	4.22	10.09	0.17	8.11 F4	CM		12.78	0.20 R	0.27 ** 0.90
	LL+I	0.30	21.05	3.11	13.84 V5			4.40	0.00	
4.23	DL+E	4.72	7.36	0.65	6.02 F1	TN	3.83		0.20 R	0.27 ** 0.90
	LL+I	0.34	-1.95	4.03	13.20 V2		3.12	0.00		
	DL+E	4.72	7.36	0.65	6.02 F1	TN		4.97	0.20 R	0.27 ** 0.90
	LL+I	0.26	-1.50	3.11	13.20 V2			4.04	0.00	
5.29	DL+E	4.05	7.18	1.39	7.31 F1	TN	2.27		0.20 R	0.27 ** 0.90
	LL+I	1.44	-2.02	4.03	13.20 V5		2.93	0.00		
	DL+E	4.05	7.18	1.39	7.31 F1	TN		2.94	0.20 R	0.27 ** 0.90
	LL+I	1.11	-1.56	3.11	13.20 V5			3.80	0.00	
6.35	DL+E	2.35	7.00	2.30	7.48 F1	TN	2.00		0.20 R	0.27 ** 0.90
	LL+I	2.57	-2.01	4.03	13.20 V5		2.71	0.00		
	DL+E	2.35	7.00	2.30	7.48 F1	TN		2.59	0.20 R	0.27 ** 0.90
	LL+I	1.98	-1.55	3.11	13.20 V5			3.51	0.00	
7.41	DL+E	-0.25	6.82	3.10	7.35 F1	TN	2.05		0.20 R	0.27 ** 0.90
	LL+I	3.70	-2.01	4.03	13.20 V5		2.51	0.00		
	DL+E	-0.25	6.82	3.10	7.35 F1	TN		2.66	0.20 R	0.27 ** 0.90
	LL+I	2.86	-1.55	3.11	13.20 V5			3.25	0.00	

SLATEFORD PRELIMINARY CULVERT RATING
 LIVE LOAD RATING W/O FWS (cont.)

SPECIAL Loading: Wall No. 1 (cont.)

Dist (ft)		Fact	Fact	Fact	Fact	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
		Moment (kips-ft)	Thrust (kips)	Shear (kips)	Resist (kips-ft) (kips)		IR STR-I	OR STR-II			
8.06	DL+E	-2.26	6.71	3.55	7.22 F1	TN	2.15		0.20 R	0.27	** 0.90
	LL+I	4.40	-2.00	4.03	13.20 V5			2.40	0.00		
	DL+E	-2.26	6.71	3.55	7.22 F1				0.20 R	0.27	** 0.90
	LL+I	3.40	-1.54	3.11	13.20 V5			2.79	0.00		
8.47	DL+E	-5.01	8.84		-47.16 F2	TN	2.01		0.79 L	0.56	0.90
	LL+I	-20.92	23.56						0.00		
	DL+E	-5.01	8.84		-47.16 F2			2.61	0.79 L	0.56	0.90
	LL+I	-16.14	18.18						0.00		
9.08	DL+E	-7.47	8.70		-41.43 F2	TN	1.45		0.79 L	0.56	0.90
	LL+I	-23.40	23.56						0.00		
	DL+E	-7.47	8.70		-41.43 F2				0.79 L	0.56	0.90
	LL+I	-18.05	18.18					1.88	0.79 L	0.56	0.90

SPECIAL Loading: Wall No. 2

Dist (ft)		Fact	Fact	Fact	Fact	Zone	Rating Factor		Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
		Moment (kips-ft)	Thrust (kips)	Shear (kips)	Resist (kips-ft) (kips)		IR STR-I	OR STR-II			
0.00	DL+E	-0.00	27.16		-3.37 F4	CM	8.21		0.20 L	0.49	** 0.90
	LL+I	-0.41	64.21						0.00		
	DL+E	-0.00	27.16		-3.37 F4			10.64	0.20 L	0.49	** 0.90
	LL+I	-0.32	49.54						0.00		
1.06	DL+E	-0.00	26.67		0.21 F4	CM	8.22		0.20 R	0.49	** 0.90
	LL+I	0.03	64.21						0.00		
	DL+E	-0.00	26.67		0.21 F4			10.65	0.20 R	0.49	** 0.90
	LL+I	0.02	49.54						0.00		
2.12	DL+E	-0.00	26.17		3.80 F4	CM	8.23		0.20 R	0.49	** 0.90
	LL+I	0.46	64.21						0.00		
	DL+E	-0.00	26.17		3.80 F4			10.66	0.20 R	0.49	** 0.90
	LL+I	0.36	49.54						0.00		
2.29	DL+E	-0.00	26.09	0.00	4.39 F4	CM	8.23		0.20 R	0.49	** 0.90
	LL+I	0.53	64.21	5.00	30.58 V5		6.11		0.00		
	DL+E	-0.00	26.09	0.00	4.39 F4			10.67	0.20 R	0.49	** 0.90
	LL+I	0.41	49.54	3.86	30.58 V5			7.92	0.00		
3.17	DL+E	-0.00	25.68	0.00	7.39 F4	CM	8.23		0.20 R	0.49	** 0.90
	LL+I	0.90	64.21	5.00	30.58 V5		6.11		0.00		
	DL+E	-0.00	25.68	0.00	7.39 F4			10.67	0.20 R	0.49	** 0.90
	LL+I	0.69	49.54	3.86	30.58 V5			7.92	0.00		
4.23	DL+E	-0.00	25.18	0.00	11.00 F4	CM	8.24		0.20 R	0.49	** 0.90
	LL+I	1.33	64.21	5.00	30.58 V5		6.11		0.00		
	DL+E	-0.00	25.18	0.00	11.00 F4			10.68	0.20 R	0.49	** 0.90
	LL+I	1.03	49.54	3.86	30.58 V5			7.92	0.00		
5.29	DL+E	-0.00	24.68	0.00	14.60 F4	CM	8.25		0.20 R	0.49	** 0.90
	LL+I	1.77	64.21	5.00	30.58 V5		6.11		0.00		
	DL+E	-0.00	24.68	0.00	14.60 F4			10.69	0.20 R	0.49	** 0.90
	LL+I	1.37	49.54	3.86	30.58 V5			7.92	0.00		
6.35	DL+E	-0.00	22.77	0.00	201.70 F1	CM	7.77		0.20 R	0.51	** 0.90
	LL+I	25.96	41.77	5.00	30.58 V5		6.11		0.00		
	DL+E	-0.00	22.77	0.00	201.70 F1			10.07	0.20 R	0.51	** 0.90
	LL+I	20.03	32.22	3.86	30.58 V5			7.92	0.00		
6.79	DL+E	-0.00	22.57	0.00	209.72 F1	CM	7.45		0.20 R	0.56	** 0.90
	LL+I	28.17	41.77	5.00	30.58 V2		6.11		0.00		
	DL+E	-0.00	22.57	0.00	209.72 F1			9.65	0.20 R	0.56	** 0.90
	LL+I	21.73	32.22	3.86	30.58 V2			7.92	0.00		
7.41	DL+E	-0.00	22.28		218.15 F1	TR	6.98		0.20 R	0.62	** 0.90
	LL+I	31.25	41.77						0.00		
	DL+E	-0.00	22.28		218.15 F1			9.05	0.20 R	0.62	** 0.90
	LL+I	24.11	32.22						0.00		
8.47	DL+E	-0.00	21.78		219.01 F1	TR	5.99		0.20 R	0.73	** 0.90
	LL+I	36.55	41.77						0.00		
	DL+E	-0.00	21.78		219.01 F1			7.77	0.20 R	0.73	** 0.90
	LL+I	28.19	32.22						0.00		
9.08	DL+E	-0.00	21.49		219.42 F1	TR	5.54		0.20 R	0.79	** 0.90
	LL+I	39.63	41.77						0.00		
	DL+E	-0.00	21.49		219.42 F1			7.18	0.20 R	0.79	** 0.90
	LL+I	30.57	32.22						0.00		

SLATEFORD PRELIMINARY CULVERT RATING
 LIVE LOAD RATING W/O FWS (cont.)

SPECIAL Loading: Wall No. 2 (cont.)

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft)	Rating Factor	Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
				(kips)	Zone	IR STR-I	OR STR-II	

SPECIAL Loading: Wall No. 3

Dist (ft)	Fact Moment (kips-ft)	Fact Thrust (kips)	Fact Shear (kips)	Fact Resist (kips-ft)	Rating Factor	Prov Reinf (in^2)	Min Reinf (in^2)	Phi Factor
				(kips)	Zone	IR STR-I	OR STR-II	
0.00	DL+E 0.36		10.12					
	LL+I -13.18		23.84	-52.96	F2	TR	4.05	0.20 L 0.54 ** 0.90
	DL+E 0.36		10.12	-52.96	F2	TR		5.25
	LL+I -10.16		18.39					0.20 L 0.54 ** 0.90
1.06	DL+E -0.00		10.58	0.93	-48.83 F4	CM	5.57	0.20 L 0.43 ** 0.90
	LL+I -8.76		27.43	-4.03	-13.84 V6		3.67	0.00
	DL+E -0.00		10.58	0.93	-48.83 F4	CM		0.20 L 0.43 ** 0.90
	LL+I -6.76		21.16	-3.11	-13.84 V6		7.22	0.00
2.12	DL+E -2.79		10.33	0.36	-36.30 F4	CM	7.32	0.20 L 0.33 ** 0.90
	LL+I -4.58		27.43	-4.03	-13.84 V6		3.52	0.00
	DL+E -2.79		10.33	0.36	-36.30 F4	CM		0.20 L 0.33 ** 0.90
	LL+I -3.53		21.16	-3.11	-13.84 V6		9.48	0.00
3.17	DL+E -4.22		10.09	-0.17	-8.10 F4	CM	9.81	0.20 L 0.27 ** 0.90
	LL+I -0.40		27.43	-4.03	-13.84 V6		3.39	0.00
	DL+E -4.22		10.09	-0.17	-8.10 F4	CM		12.71 0.20 L 0.27 ** 0.90
	LL+I -0.31		21.16	-3.11	-13.84 V6		4.40	0.00
4.23	DL+E -4.72		7.36	-0.65	-6.03 F2	TN	3.84	0.20 L 0.27 ** 0.90
	LL+I -0.34		-1.94	-4.03	-13.20 V1		3.12	0.00
	DL+E -4.72		7.36	-0.65	-6.03 F2	TN		4.98 0.20 L 0.27 ** 0.90
	LL+I -0.26		-1.50	-3.11	-13.20 V1		4.04	0.00
5.29	DL+E -4.05		7.18	-1.39	-7.31 F2	TN	2.27	0.20 L 0.27 ** 0.90
	LL+I -1.44		-2.02	-4.03	-13.20 V6		2.93	0.00
	DL+E -4.05		7.18	-1.39	-7.31 F2	TN		2.94 0.20 L 0.27 ** 0.90
	LL+I -1.11		-1.56	-3.11	-13.20 V6		3.80	0.00
6.35	DL+E -2.35		7.00	-2.30	-7.48 F2	TN	2.00	0.20 L 0.27 ** 0.90
	LL+I -2.57		-2.01	-4.03	-13.20 V6		2.71	0.00
	DL+E -2.35		7.00	-2.30	-7.48 F2	TN		2.59 0.20 L 0.27 ** 0.90
	LL+I -1.98		-1.55	-3.11	-13.20 V6		3.51	0.00
7.41	DL+E 0.25		6.82	-3.10	-7.35 F2	TN	2.05	0.20 L 0.27 ** 0.90
	LL+I -3.70		-2.00	-4.03	-13.20 V6		2.51	0.00
	DL+E 0.25		6.82	-3.10	-7.35 F2	TN		2.66 0.20 L 0.27 ** 0.90
	LL+I -2.86		-1.55	-3.11	-13.20 V6		3.25	0.00
8.04	DL+E 2.20		6.71	-3.53	-7.22 F2	TN	2.15	0.20 L 0.27 ** 0.90
	LL+I -4.38		-2.00	-4.03	-13.20 V6		2.40	0.00
	DL+E 2.20		6.71	-3.53	-7.22 F2	TN		2.78 0.20 L 0.27 ** 0.90
	LL+I -3.38		-1.55	-3.11	-13.20 V6		3.11	0.00
8.47	DL+E 5.01		8.84		47.62 F1	TN	2.04	0.79 R 0.56 0.90
	LL+I 20.92		23.84					
	DL+E 5.01		8.84		47.62 F1	TN		2.64 0.79 R 0.56 0.90
	LL+I 16.14		18.39					
9.08	DL+E 7.47		8.70		41.73 F1	TN	1.46	0.79 R 0.56 0.90
	LL+I 23.40		23.84					
	DL+E 7.47		8.70		41.73 F1	TN		1.90 0.79 R 0.56 0.90
	LL+I 18.05		18.39					

** Warning: The provided area of steel is less than the required minimum area of steel.

SLATEFORD PRELIMINARY CULVERT RATING
LIVE LOAD RATING W/O FWS (cont.)

F or V reported after the Fact Resist indicates whether the Rating is for Flexure (F) or Shear (V). The numerical code reported after F or V corresponds to the governing Maximum Effect Case for the Rating Factor.

Maximum Effect Cases:

- | | | |
|---|---------------------|------------------------------|
| 1 | Maximum Positive | Moment and Concurrent Thrust |
| 2 | Maximum Negative | Moment and Concurrent Thrust |
| 3 | Maximum Tension | Thrust and Concurrent Moment |
| 4 | Maximum Compression | Thrust and Concurrent Moment |
| 5 | Maximum Positive | Shear and Concurrent Moment |
| 6 | Maximum negative | Shear and Concurrent Moment |

T, B, L, or R reported after the Reinforcement (Reinf) indicates the location of the flexural reinforcement reported:

- | | |
|---|------------------------|
| T | Top steel in a slab |
| B | Bottom steel in a slab |
| L | Left steel in a wall |
| R | Right steel in a wall |

Zone Code Descriptions

- | | |
|----|----------------------------------|
| TN | - Tension controlled section |
| TR | - Transition section |
| CM | - Compression controlled section |

Phi Factor Epsilon (cl) = 0.00200
Phi Factor Epsilon (tl) = 0.00500

Note: Wall distances begin at the bottom of the wall and slab distances begin at the left side of the slab.

SLATEFORD PRELIMINARY CULVERT RATING
 STRIP FOOTING PERFORMANCE RATIOS W/O FWS

Wall No. 1

Dist (ft)	Flexure Loading				Moment	Shear Loading	Moment	Shear Loading	Shear Perf				
	Code	Fact	Moment	Resist	Phi Factor	Perf Ratio	Code	Shear	Resist	Ratio			
	A	B	C	D	(kips-ft)	(kips-ft)	A	B	C	D	(kips)	(kips)	
1.66L							1	1	7	2	-5.23	-21.42	4.10
0.00LT	1	1	7	2	20.31	39.25	0.90	1.93	1	6	7	2	4.35
LB	1	1	7	2	20.31	39.25	0.90	1.93					21.42
0.00RT	1	4	7	2	12.42	39.25	0.90	3.16					4.92
RB	1	4	7	2	12.42	39.25	0.90	3.16					
1.66R							1	2	7	2	1.55	21.42	13.77

Wall No. 2

Dist (ft)	Flexure Loading				Moment	Shear Loading	Moment	Shear Loading	Shear Perf				
	Code	Fact	Moment	Resist	Phi Factor	Perf Ratio	Code	Shear	Resist	Ratio			
	A	B	C	D	(kips-ft)	(kips-ft)	A	B	C	D	(kips)	(kips)	
1.66L							1	5	7	2	-4.30	-21.42	4.98
0.00LT	1	4	7	2	27.84	39.25	0.90	1.41					
LB	1	4	7	2	27.84	39.25	0.90	1.41					
0.00RT	1	4	7	2	28.39	39.25	0.90	1.38					
RB	1	4	7	2	28.39	39.25	0.90	1.38					
1.66R							1	6	7	2	4.31	21.42	4.97

Wall No. 3

Dist (ft)	Flexure Loading				Moment	Shear Loading	Moment	Shear Loading	Shear Perf				
	Code	Fact	Moment	Resist	Phi Factor	Perf Ratio	Code	Shear	Resist	Ratio			
	A	B	C	D	(kips-ft)	(kips-ft)	A	B	C	D	(kips)	(kips)	
1.66L							1	1	7	2	-1.55	-21.42	13.78
0.00LT	1	4	7	2	12.45	39.25	0.90	3.15					
LB	1	4	7	2	12.45	39.25	0.90	3.15					
0.00RT	1	2	7	2	20.14	39.25	0.90	1.95	1	5	7	2	-4.35
RB	1	2	7	2	20.14	39.25	0.90	1.95					
1.66R							1	2	7	2	5.19	21.42	4.13

L or R after the distance indicates the Left or Right side of the strip footing.

T or B after the distance indicates the location of the flexural reinforcement reported:

T Top steel in footing
 B Bottom steel in footing

Flexure/Shear Loading Codes:

Code A	Code B	Code C	Code D
1 Strength-I	1 Maximum Positive Moment	1 PHL-93	1 On Deck
2 Strength-II	2 Maximum Negative Moment	2 HL-93	2 Thru Fill
3 Strength-IA	3 Maximum Tension Thrust	3 P-82	
	4 Maximum Compression Thrust	4 ML-80	
	5 Maximum Positive Shear	5 HS-20	
	6 Maximum Negative Shear	6 H-20	
		7 SLL	
		8 TK527	
		9 EV2	
		Z EV3	
		Y SU6TV	
		X PA2016-13	

SLATEFORD PRELIMINARY CULVERT RATING
RATING SUMMARY W/O FWS

Loading: SPECIAL

Member	No.	Dist	Dist/	IR	IR	Dist/	OR	OR
			Span (ft)	Rating STR-I	Rating Tonnage (ton)	Span (ft)	Rating Factor	Tonnage STR-II (ton)
Top Slab	1	5.60	0.40	0.61 F	345.43	5.60	0.40	0.79 F 447.78
Top Slab	2	8.40	0.60	0.61 F	345.40	8.40	0.60	0.79 F 447.74
Wall	1	9.08	0.86	1.45 F	824.29	9.08	0.86	1.88 F 999.99
Wall	2	9.08	0.86	5.54 F	999.99	9.08	0.86	7.18 F 999.99
Wall	3	9.08	0.86	1.46 F	831.46	9.08	0.86	1.90 F 999.99

The Minimum Inventory Rating is governed by FLEXURE.

The Minimum Inventory Rating Factor is 0.61 at Distance 8.40 (ft)
in: Top Slab 2

The Minimum Operating Rating is governed by FLEXURE.

The Minimum Operating Rating Factor is 0.79 at Distance 8.40 (ft)
in: Top Slab 2

F or V reported after the Rating Factor indicates whether the Rating
is for Flexure (F) or Shear (V).

Note: Wall distances begin at the bottom of the wall and slab distances
begin at the left side of the slab.

SLATEFORD PRELIMINARY CULVERT RATING
RATING SUMMARY W/O FWS (cont.)

+-----
+
+ C O M B I N E D +
+ R A T I N G S U M M A R Y +
+-----

SPECIAL
INVENTORY Member Top Slab 2
RATING Dist. (ft) 8.40
(IR) Limit State STR-I
Rating 0.61 F
Rating Tons 345.40

SPECIAL
OPERATING Member Top Slab 2
RATING Dist. (ft) 8.40
(OR) Limit State STR-II
Rating 0.79 F
Rating Tons 447.74

All ratings are based on the exclusion of the design future wearing surface.

F or V reported after the Rating Factor indicates whether the Rating
is for Flexure (F) or Shear (V).

SLATEFORD PRELIMINARY CULVERT RATING
 MINIMUM REINFORCEMENT CHECK

Top Slab No. 1 - Top Face

Cracking Moment Dist (ft)	M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp Shrink Area (in^2)	0.002 Ag (in^2)	Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
1.50	42.14+	-7.64	0.14	0.45*	N/A	0.900	1.270	
2.80	42.14+	-0.78	0.01	0.45*	N/A	0.900	1.270	
3.29	42.14+			0.45*	N/A		1.270	
4.20	42.14+			0.45*	N/A		1.270	
5.60	42.14+			0.45*	N/A		1.270	
7.00	42.14+	-1.11	0.02	0.45*	N/A	0.900	1.270	
8.40	42.14+	-6.11	0.12	0.45*	N/A	0.900	1.270	
9.80	42.14+	-14.27	0.27	0.45*	N/A	0.900	1.270	
10.71	42.14+	-32.65	0.62*	0.45	N/A	0.900	1.270	
11.20	42.14	-44.81+	0.81*	0.45	N/A	0.900	1.270	
12.50	42.14	-81.75+	0.81*	0.45	N/A	0.900	1.270	

Top Slab No. 1 - Bottom Face

Cracking Moment Dist (ft)	M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp Shrink Area (in^2)	0.002 Ag (in^2)	Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
1.50	42.14+	29.72	0.57*	0.45	N/A	0.900	0.790	
2.80	42.14	56.02+	0.81*	0.45	N/A	0.900	0.790	A
3.29	42.14	63.27+	0.81*	0.45	N/A	0.900	0.790	A
4.20	42.14	75.65+	0.81*	0.45	N/A	0.900	0.790	A
5.60	42.14	85.56+	0.81*	0.45	N/A	0.900	0.790	A
7.00	42.14	82.68+	0.81*	0.45	N/A	0.900	0.790	A
8.40	42.14	66.10+	0.81*	0.45	N/A	0.900	0.790	A
9.80	42.14+	37.16	0.71*	0.45	N/A	0.900	0.790	
10.71	42.14+	14.21	0.27	0.45*	N/A	0.900	0.790	
11.20	42.14+	5.25	0.10	0.45*	N/A	0.900	0.790	
12.50	42.14+			0.45*	N/A		0.790	

Top Slab No. 2 - Top Face

Cracking Moment Dist (ft)	M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp Shrink Area (in^2)	0.002 Ag (in^2)	Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
1.50	42.14	-81.74+	0.81*	0.45	N/A	0.900	1.270	
2.80	42.14	-44.82+	0.81*	0.45	N/A	0.900	1.270	
3.29	42.14+	-32.64	0.62*	0.45	N/A	0.900	1.270	
4.20	42.14+	-14.26	0.27	0.45*	N/A	0.900	1.270	
5.60	42.14+	-6.11	0.12	0.45*	N/A	0.900	1.270	
7.00	42.14+	-1.11	0.02	0.45*	N/A	0.900	1.270	
8.40	42.14+			0.45*	N/A		1.270	
9.80	42.14+			0.45*	N/A		1.270	
10.71	42.14+			0.45*	N/A		1.270	
11.20	42.14+	-0.78	0.01	0.45*	N/A	0.900	1.270	
12.50	42.14+	-7.64	0.14	0.45*	N/A	0.900	1.270	

Top Slab No. 2 - Bottom Face

Cracking Moment Dist (ft)	M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp Shrink Area (in^2)	0.002 Ag (in^2)	Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
1.50	42.14+			0.45*	N/A		0.790	
2.80	42.14+	5.26	0.10	0.45*	N/A	0.900	0.790	
3.29	42.14+	14.22	0.27	0.45*	N/A	0.900	0.790	
4.20	42.14+	37.17	0.71*	0.45	N/A	0.900	0.790	
5.60	42.14	66.10+	0.81*	0.45	N/A	0.900	0.790	A
7.00	42.14	82.69+	0.81*	0.45	N/A	0.900	0.790	A
8.40	42.14	85.56+	0.81*	0.45	N/A	0.900	0.790	A
9.80	42.14	75.65+	0.81*	0.45	N/A	0.900	0.790	A
10.71	42.14	63.27+	0.81*	0.45	N/A	0.900	0.790	A
11.20	42.14	56.03+	0.81*	0.45	N/A	0.900	0.790	A
12.50	42.14+	29.71	0.57*	0.45	N/A	0.900	0.790	

SLATEFORD PRELIMINARY CULVERT RATING
 MINIMUM REINFORCEMENT CHECK (cont.)

Top Slab No. 2 - Bottom Face (cont.)

Wall No. 1 - Left Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp		Phi Factor (in^2)	Area Width (in^2)	Status Code
				Min (in^2)	Shrink (in^2)			
0.00	16.46+	-12.39	0.42*	0.27	N/A	0.900	0.790	
1.06	16.46+	-4.86	0.16	0.27*	N/A	0.900	0.790	
2.12	16.46+	-0.85	0.03	0.27*	N/A	0.900	0.790	
3.17	16.46+			0.27*	N/A		0.790	
4.23	16.46+	-3.46	0.11	0.27*	N/A	0.900	0.790	
5.29	16.46+	-10.37	0.35*	0.27	N/A	0.900	0.790	
6.35	16.46	-17.86+	0.56*	0.27	N/A	0.900	0.790	
7.41	16.46	-25.87+	0.56*	0.27	N/A	0.900	0.790	
8.06	16.46	-31.06+	0.56*	0.27	N/A	0.900	0.790	
8.47	16.46	-34.57+	0.56*	0.27	N/A	0.900	0.790	
9.08	16.46	-41.16+	0.56*	0.27	N/A	0.900	0.790	

Wall No. 1 - Right Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp		Phi Factor (in^2)	Area Width (in^2)	Status Code
				Min (in^2)	Shrink (in^2)			
0.00	16.46	17.09+	0.54*	0.27	N/A	0.900	0.200	A
1.06	16.46+	13.15	0.43*	0.27	N/A	0.900	0.200	A
2.12	16.46+	9.92	0.33*	0.27	N/A	0.900	0.200	A
3.17	16.46+	6.35	0.21	0.27*	N/A	0.900	0.200	A
4.23	16.46+	6.75	0.22	0.27*	N/A	0.900	0.200	A
5.29	16.46+	7.32	0.24	0.27*	N/A	0.900	0.200	A
6.35	16.46+	6.56	0.21	0.27*	N/A	0.900	0.200	A
7.41	16.46+	4.60	0.15	0.27*	N/A	0.900	0.200	A
8.06	16.46+	2.85	0.09	0.27*	N/A	0.900	0.200	A
8.47	16.46+	1.82	0.06	0.27*	N/A	0.900	0.200	A
9.08	16.46+	1.10	0.04	0.27*	N/A	0.900	0.200	A

Wall No. 2 - Left Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp		Phi Factor (in^2)	Area Width (in^2)	Status Code
				Min (in^2)	Shrink (in^2)			
0.00	65.85+	-8.48	0.12	0.49*	N/A	0.900	0.200	A
1.06	65.85+	-2.70	0.04	0.49*	N/A	0.900	0.200	A
2.12	65.85+	-6.68	0.10	0.49*	N/A	0.900	0.200	A
2.29	65.85+	-7.76	0.11	0.49*	N/A	0.900	0.200	A
3.17	65.85+	-13.45	0.20	0.49*	N/A	0.900	0.200	A
4.23	65.85+	-20.50	0.30	0.49*	N/A	0.900	0.200	A
5.29	65.85+	-27.55	0.41	0.49*	N/A	0.900	0.200	A
6.35	65.85+	-34.61	0.51*	0.49	N/A	0.900	0.200	A
6.79	65.85+	-37.56	0.56*	0.49	N/A	0.900	0.200	A
7.41	65.85+	-41.67	0.62*	0.49	N/A	0.900	0.200	A
8.47	65.85+	-48.73	0.73*	0.49	N/A	0.900	0.200	A
9.08	65.85+	-52.84	0.79*	0.49	N/A	0.900	0.200	A

Wall No. 2 - Right Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Rho Area (in^2)	Temp		Phi Factor (in^2)	Area Width (in^2)	Status Code
				Min (in^2)	Shrink (in^2)			
0.00	65.85+	8.48	0.12	0.49*	N/A	0.900	0.200	A
1.06	65.85+	2.70	0.04	0.49*	N/A	0.900	0.200	A
2.12	65.85+	6.68	0.10	0.49*	N/A	0.900	0.200	A
2.29	65.85+	7.76	0.11	0.49*	N/A	0.900	0.200	A
3.17	65.85+	13.45	0.20	0.49*	N/A	0.900	0.200	A
4.23	65.85+	20.50	0.30	0.49*	N/A	0.900	0.200	A
5.29	65.85+	27.55	0.41	0.49*	N/A	0.900	0.200	A
6.35	65.85+	34.61	0.51*	0.49	N/A	0.900	0.200	A

SLATEFORD PRELIMINARY CULVERT RATING
 MINIMUM REINFORCEMENT CHECK (cont.)

Wall No. 2 - Right Face (cont.)

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Temp		Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
			Rho Min (in^2)	Shrink (in^2)			
6.79	65.85+	37.56	0.56*	0.49	N/A	0.900	0.200 A
7.41	65.85+	41.67	0.62*	0.49	N/A	0.900	0.200 A
8.47	65.85+	48.73	0.73*	0.49	N/A	0.900	0.200 A
9.08	65.85+	52.84	0.79*	0.49	N/A	0.900	0.200 A

Wall No. 3 - Left Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Temp		Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
			Rho Min (in^2)	Shrink (in^2)			
0.00	16.46	-17.09+	0.54*	0.27	N/A	0.900	0.200 A
1.06	16.46+	-13.15	0.43*	0.27	N/A	0.900	0.200 A
2.12	16.46+	-9.92	0.33*	0.27	N/A	0.900	0.200 A
3.17	16.46+	-6.35	0.21	0.27*	N/A	0.900	0.200 A
4.23	16.46+	-6.75	0.22	0.27*	N/A	0.900	0.200 A
5.29	16.46+	-7.32	0.24	0.27*	N/A	0.900	0.200 A
6.35	16.46+	-6.56	0.21	0.27*	N/A	0.900	0.200 A
7.41	16.46+	-4.60	0.15	0.27*	N/A	0.900	0.200 A
8.04	16.46+	-2.92	0.09	0.27*	N/A	0.900	0.200 A
8.47	16.46+	-1.82	0.06	0.27*	N/A	0.900	0.200 A
9.08	16.46+	-1.10	0.04	0.27*	N/A	0.900	0.200 A

Wall No. 3 - Right Face

Dist (ft)	Cracking Moment M(cr) (kip-ft)	4/3*M(u) (kip-ft)	Temp		Phi Factor (in^2)	Area Prov/ Width (in^2)	Status Code
			Rho Min (in^2)	Shrink (in^2)			
0.00	16.46+	12.39	0.42*	0.27	N/A	0.900	0.790
1.06	16.46+	4.86	0.16	0.27*	N/A	0.900	0.790
2.12	16.46+	0.85	0.03	0.27*	N/A	0.900	0.790
3.17	16.46+			0.27*	N/A		0.790
4.23	16.46+	3.46	0.11	0.27*	N/A	0.900	0.790
5.29	16.46+	10.37	0.35*	0.27	N/A	0.900	0.790
6.35	16.46	17.87+	0.56*	0.27	N/A	0.900	0.790
7.41	16.46	25.88+	0.56*	0.27	N/A	0.900	0.790
8.04	16.46	30.89+	0.56*	0.27	N/A	0.900	0.790
8.47	16.46	34.58+	0.56*	0.27	N/A	0.900	0.790
9.08	16.46	41.16+	0.56*	0.27	N/A	0.900	0.790

Status Code Descriptions

+ - Controlling moment for Rho Min Area calculation

* - Controlling minimum area of steel

A - Area provided smaller than required minimum area of steel

SLATEFORD PRELIMINARY CULVERT RATING
 STRIP FOOTING BEARING PRESSURE

Wall No. 1

Live Load	Locn	STR-I e/B Ratio	STR-I Bearing Pressure (ksf)	STR-II e/B Ratio	STR-II Bearing Pressure (ksf)	SER-I e/B Ratio	SER-I Bearing Pressure (ksf)
SPECIAL	L	-0.16 *	12.38	-0.13	10.55	-0.09	7.50
	R		6.00		5.65		4.24

L Left edge of the footing

R Right edge of the footing

A maximum value for qb of 9.67 (ksf) (qb = N/Be) occurs for the STR-I limit state, SPECIAL live load, maximum effect case 1. For this reported condition, Be is 4.40 (ft). This average pressure is used in the calculation of settlement for soils.

Wall No. 2

Live Load	Locn	STR-I e/B Ratio	STR-I Bearing Pressure (ksf)	STR-II e/B Ratio	STR-II Bearing Pressure (ksf)	SER-I e/B Ratio	SER-I Bearing Pressure (ksf)
SPECIAL	L	-0.04	14.26	-0.04	12.04	-0.04	9.10
	R		14.61 *		12.31 *		9.30 *

L Left edge of the footing

R Right edge of the footing

A maximum value for qb of 14.49 (ksf) (qb = N/Be) occurs for the STR-I limit state, SPECIAL live load, maximum effect case 4. For this reported condition, Be is 6.47 (ft). This average pressure is used in the calculation of settlement for soils.

Wall No. 3

Live Load	Locn	STR-I e/B Ratio	STR-I Bearing Pressure (ksf)	STR-II e/B Ratio	STR-II Bearing Pressure (ksf)	SER-I e/B Ratio	SER-I Bearing Pressure (ksf)
SPECIAL	L	0.16	6.01	0.13 *	5.66	0.09 *	4.25
	R		12.31		10.50		7.47

L Left edge of the footing

R Right edge of the footing

A maximum value for qb of 9.61 (ksf) (qb = N/Be) occurs for the STR-I limit state, SPECIAL live load, maximum effect case 6. For this reported condition, Be is 4.39 (ft). This average pressure is used in the calculation of settlement for soils.

* Indicates the maximum e/B Ratio and Footing Pressure, among all maximum effect cases, for each limit state.

SLATEFORD PRELIMINARY CULVERT RATING
QUANTITIES

Volume of Concrete

Based on a segment length of: 82.50 ft.

Top Slab:	201.67	(yd ³)
Left Wall:	40.42	(yd ³)
Interior Wall:	80.84	(yd ³)
Right Wall:	40.42	(yd ³)
Haunches:	13.75*	(yd ³)
Strip Footing:	99.31	(yd ³)
TOTAL:	476.41	(yd ³)

* All haunches are included only in this total

SLATEFORD PRELIMINARY CULVERT RATING

Table of Contents

Description	Page
SUMMARY OF INPUT FILE.....	2
ADDITIONAL INFORMATION.....	7
COMPUTED VALUES.....	7
ADDITIONAL GEOMETRY.....	7
LIVE LOAD ELAT & IM TABLE.....	8
Dynamic Load Allowance.....	8
Case 1 - On Deck Loading.....	8
Case 2 - Thru Fill Loading.....	8
SERVICEABILITY SPACING SUMMARY.....	9
LIVE LOAD RATING W/O FWS.....	10
SPECIAL Loading: Top Slab No. 1.....	10
SPECIAL Loading: Top Slab No. 2.....	10
SPECIAL Loading: Wall No. 1.....	11
SPECIAL Loading: Wall No. 2.....	12
SPECIAL Loading: Wall No. 3.....	13
STRIP FOOTING PERFORMANCE RATIOS W/O FWS.....	15
Wall No. 1.....	15
Wall No. 2.....	15
Wall No. 3.....	15
RATING SUMMARY W/O FWS.....	16
MINIMUM REINFORCEMENT CHECK.....	18
Top Slab No. 1 - Top Face.....	18
Top Slab No. 1 - Bottom Face.....	18
Top Slab No. 2 - Top Face.....	18
Top Slab No. 2 - Bottom Face.....	18
Wall No. 1 - Left Face.....	19
Wall No. 1 - Right Face.....	19
Wall No. 2 - Left Face.....	19
Wall No. 2 - Right Face.....	19
Wall No. 3 - Left Face.....	20
Wall No. 3 - Right Face.....	20
STRIP FOOTING BEARING PRESSURE.....	21
Wall No. 1.....	21
Wall No. 2.....	21
Wall No. 3.....	21
QUANTITIES.....	22

Volume of Concrete.....	22
Based on a segment length of: 82.50 ft.....	22

History of Reinforcing Steel

[Home \(/index.cfm\)](#) > [Reinforcing Basics \(<http://www.crsi.org/index.cfm/basics>\)](#) > [Reinforcing Steel \(/index.cfm/basics/reinforcing-steel\)](#) > [History of Reinforcing Steel \(/index.cfm/basics/history-of-reinforcing-steel\)](#)

Reinforcing Steel Timeline

Historical Resources

(<http://resources.crsi.org/resources-search/?tag=Historical>)


Year Event

- 1910** First reinforcing bar specifications issued.
- 1911** ASTM A15 published with grades 33 and 50.
- 1914** ASTM A15 revised by adding grade 40.
- 1924** The American Association of State Highway Officials (AASHO) issued its first standard for concrete reinforcement, AASHO M 31.
- 1928** First hot-dip galvanized reinforcing bar specifications published, ASTM A123.
- 1947** ASTM A305 published; it included rebar deformation patterns.
- 1953** U.S. Navy uses galvanized rebar in a bridge in Bermuda.
- 1957** ASTM A408 published; it covered large diameter bars (no.14 and no.18 bars) in three different grades.
- 1958** ASTM A431 published; it included grade 75 rebar.
- 1959** ASTM A432 published; it included grade 60 rebar.
- 1968** ASTM A305, ASTM A408, ASTM A431, and ASTM A432 withdrawn. ASTM A615 published (replaced ASTM A15, ASTM A408, ASTM A431, ASTM A432, and portions of ASTM A305) with grades 40, 60, and 75.
- 1969** ASTM A15 withdrawn.
- 1972** ASTM A615 revised, removing grade 75 rebar.
- 1973** Epoxy-coated rebar first used in a U.S. bridge.
- 1974** ASTM A706 published for rebars with improved weldability.
- 1979** ASTM A767 published for zinc-coated (galvanized) rebars.
- 1981** ASTM A775 for epoxy-coated rebars and ASTM D3963 for handling of epoxycoated bars published.

- 1982** The American Association of State Highway and Transportation Officials (AASHTO) published the metric version of standard M31, known as AASHTO M 31M.
- 1983** Stainless steel rebar first used in U.S. bridges.
- 1987** ASTM A615 revised, reinstating grade 75. AASHTO published M 284 for epoxy-coated rebars.
- 1989** ASTM A775/A775M revised to change damage threshold and add anchor profile.
- 1990** ASTM A775/A775M revised with provisions for repairing damaged coating.
FHWA memorandum issued on certification programs.
- 1991** The Concrete Reinforcing Steel Institute (CRSI) began a certification program for epoxy-coating applicator plants.
- 1992** ASTM A775/A775M revised to change the coating thickness.
- 1994** ASTM A775/A775M revised to change the bend tests.
- 1995** ASTM A934/A934M published for prefabricated epoxy-coated rebar. ASTM A775/A75M revised to allow a chemical wash for surface preparation.
- 1996** ASTM A955/A955M published for stainless steel rebars.
- 1997** Cathodic debonding introduced in ASTM A775/A775M and A934/A934M.
- 2001** AASHTO issued AASHTO M 317M/M 317.
- 2003** ASTM A995 revised.
- 2004** ASTM A1035/A1035M published.
ASTM A615/A615M renamed.
ASTM A775/775M revised.
AASHTO MP 13M/MP 13 published.
- 2007** ASTM A955 revised.
- 2008** ASTM A1055 published for zinc and epoxy dual coated rebars.
- 2009** STM A615/A615M revised, adding grade 80.
ASTM A706/A706M revised, adding grade 80.
AASHTO MP 18M/MP 18 published.
- 2012** AASHTO discontinued AASHTO M 284M/M 284. It was replaced by ASTM A775/A775M.
AASHTO discontinued AASHTO M 317M/M 317. It was replaced by ASTM D3963/D3963M.

- 2015** ASTM A615/A615M revised, adding grade 100.
ASTM A1035/A1035M revised.
ASTM A1094/A1094M published for continuous hot-dip galvanized steel rebars.
AASHTO updated AASHTO MP 18M/MP 18.


NOTE: Information based on FHWA Publication No.: FHWA-HRT-16-012




[\(/index.cfm/members-only\)](#)

© 2019 CRSI | [Sitemap \(/sitemap.cfm\)](#) | [Privacy Policy \(/index.cfm/privacy\)](#) | [Design/Hosted InteractiveTwist](#)
[\(http://www.interactivetwist.com\)](#)

Loading



Cooper E-80 Loading



One E-80 (Locomotive) Axle =
Highway Truck (HS-20)!

Alternate Live Load

AREMA

COPYRIGHT © AREMA 2010

15 23 of 32

Standard gauge [edit]

Main article: Standard-gauge railway

In common usage the term "standard gauge" refers to 1,435 mm (4 ft 8½ in).

Concrete @ your Fingertips

[Return](#)[New search \(fingertips.asp\)](#)[Print \(fingertips-print.asp?docid=737\)](#)[e-mail a friend \(fingertips-forward.asp?docid=737\)](#)

Strength of historic concrete

The strength of the concrete in historic structures is likely to be very variable. The only sure way of determining it is to carry out appropriate tests (see **Testing/Hardened concrete/Core testing for strength**). However, if design information is available, guidance on the likely minimum concrete strength may be obtained from the Codes of Practice current at the time.

CP 114, *Structural use of reinforced concrete in buildings*, which was first published in 1948, specified three nominal concrete mixes on the basis of cement: fine aggregate: coarse aggregate ratios by volume, namely 1:1:2, 1:1½:3 and 1:2:4. Minimum 28-day cube strengths for the three mixes were given as 4500, 3750 and 3000lb/sq. inch respectively (i.e. approximately 31, 26 and 21N/mm²).

CP 115, *The structural use of prestressed concrete in buildings*, which was first published in 1959, specified minimum 28-day cube strengths of 6000lb/sq. inch (approximately 41N/mm²) for pre-tensioned concrete and 4500lb/sq. inch (approximately 31N/mm²) for post-tensioned concrete.

CP 116, *The structural use of precast concrete*, published in 1965, specified 5 grades of concrete ranging from Grade A (3000lb/sq. inch or approximately 21N/mm²) to Grade E (7500lb/sq. inch or approximately 52N/mm²).

CP110, *The structural use of concrete*, was published in 1972. Described as "The Unified Code" it brought together the separate codes relating to reinforced, prestressed and precast concrete. Design in CP 110 (and all subsequent Codes) was based on specified concrete grades. Minimum concrete grades were specified for different types of element: 20N/mm² for reinforced concrete, 30N/mm² for post-tensioned prestressed concrete and 40N/mm² for pre-tensioned prestressed concrete.

Further information may be found in Concrete Society Technical Report 70, *Historical approaches to the design of concrete buildings and structures*, which also includes information on likely steel strengths, allowable materials etc.

Other references: Scott, WL, Glanville, W and Thomas, FG. *Explanatory handbook on the BS Code of Practice for reinforced concrete*, 1950 (revised 1957)

Walley, F and Bate, SCC. *A guide to the BS Code of Practice for prestressed concrete CP 115: 1959, 1961*

Bate, SCC et al. *Handbook to the unified Code for structural concrete (CP110: 1972)*, 1972.

Concrete Bookshop - *Members receive 40% discount on Concrete Society publications*




TR70 Historical approaches to the design of concrete buildings and structures

Buy now (<http://www.concretebookshop.com/tr70-historical-approaches-to-the-design-of-concrete-buildings-and-structures-1869-p.asp>)

Privacy policy (<http://www.concrete.org.uk/privacy.asp>)

511660

F.R.




CROSS SECTION

SCALE: $\frac{1}{30} = 1'-0''$

Box shall be Class A Concrete.


QUANTITIES

- 7.1 C.Y. Class A Concrete per lineal foot.
- 9.5 Lbs Plain Steel Bars



PLAN

SCALE: $\frac{1}{30} = 1'-0''$



JOINT DETAILS

SCALE: $\frac{1}{30} = 1'-0''$

Box shall be Class A Concrete.

COMMONWEALTH OF PENNSYLVANIA

DEPARTMENT OF HIGHWAYS

R.C. DOUBLE BOX CULVERT

2-14'-0" SPANS 9'-0" CLEAR

STA. 1187+58 R166-8 NORTHAMPTON CO.

SCALES AS SHOWN

DESIGNED BY H.E.M. CHECKED BY S.E.P.M. 10-14-35 L-352

BMS 48-0611-0600-1282

A

5

B

C

!